

PLUMETT Y-CONNECTOR

Y-connectors are an accessory for the MiniJet, CableJet and SuperJet allowing to install a second cable, under favourable conditions even a third cable, in a duct already occupied by a cable. Provided that the duct section is sufficient.

One branch of the Y-connector, connected to the MiniJet, CableJet or SuperJet, is used for feeding the second cable in the duct.

The cable already installed in the duct is put in the second branch of the Y-connector, where it is fastened and sealed.



Y 40-40-18

Duct inserts, sealing rings and duct clamps are included.



Y 50-50-18

Duct inserts, sealing rings and duct clamps are included.



Y Standard

Cable and duct inserts and duct clamps are not included.
Various sizes are available.

Standard equipment:

1 operation and maintenance manual

Standard version	Y-Connector	Y-Connector	Y-Connector
Type	40/40/18	50/50/18	Standard
Application	MiniJet/CableJet/ SuperJet	MiniJet/CableJet/ SuperJet	MiniJet/CableJet/ SuperJet
Cable dia. [mm]	6-18	6-18	9-36
Duct OD [mm]	40	50	20-63
Max. air pressure [bar]	12	12	12
Length [mm]	310	310	355
Width [mm]	205	205	290
Height [mm]	95	95	182
Total weight [kg]	4.7	4.7	13

Specifications are subject to change without notice